

<b>Technical Data</b>		<b>Audi Q4 e-tron 40 150 kW</b>	
<b>Program for Germany</b>		Status: 06/22/21	
<b>Engine / electrics</b>			
Peak electrical output in kW (PS)		150 (204)	
Continuous electrical output in kW		70	
Electrical torque output in Nm ( <i>lb-ft</i> )		310 (228.6)	
Battery type		Lithium-ion	
Battery capacity gross / net in kWh		82 / 76.6	
12V-Battery in A / Ah		280 / 51	
On-board voltage 1 in volts		12	
On-board voltage 3 in volts		400	
<b>Drivetrain / transmission</b>			
Drive type		Rear-wheel drive	
Transmission type		1-speed / automatic	
<b>Suspension / steering / brakes</b>			
Type and design of front-axle suspension		MacPherson struts, front	
Type and design of rear-axle suspension		4-link rear axle	
Steering		Electromechanical steering with speed-dependent power assistance	
Steering ratio		15.6	
Turning circle in m ( <i>ft</i> )		10.2 (33.5)	
Brake control system		Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic) front   rear		235/55 R 19   255/50 R 19	
Wheels (basic) front   rear		Steel 8 J x 19"   8 J x 19"	
<b>Performance / acoustics</b>			
Top speed in km/h ( <i>mph</i> )		160 (99.4)	
Limited		yes	
Electrical acceleration, 0-100 km/h ( <i>62.1 mph</i> ) in s		8.5	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)		- / 66	
<b>Consumption / range</b>			
Electric power consumption, combined, in kWh/100 km ( <i>62.1 mi</i> )*		20.1 - 17.3 (WLTP) 17.7 - 16.3 (NEDC)	
CO2 emissions, combined, in g/km ( <i>g/mi</i> )		0	
Electrical range, combined according to WLTP in km ( <i>mi</i> )*		520 - 446 (323.1 - 277.1)	
<b>Servicing / guarantee (Germany)</b>			
Service interval		2 years	
Vehicle / paint / rust perforation guarantee		2 / 3 / 12 (years)	
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive		16 / 22 / 22	
<b>Weights / loads</b>			
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )		2050 (4519.5) / 2125 (4684.8) / 2640 (5820.2)	
Front/rear axle load limit in kg ( <i>lb</i> )		1195 (2634.5) / 1505 (3318.0)	
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )		1000 (2204.6) / 1000 (2204.6) // 750 (1653.5)	
Roof load limit / permissible nose weight in kg ( <i>lb</i> )		75 (165.3) / 75 (165.3)	

<b>Capacities</b>	
Cooling system capacity (incl. heating) in l (US gal)	10.3 (2.7)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> (sq ft)	0.28 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4588 (15.1) / 1865 (6.1) / 1632 (5.4) / -
Width including mirrors in mm (ft)	2108 (6.9)
Wheelbase / track width front/rear in mm (ft)	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	19.40 / 16.90
Height of loading edge with steel springs / air springs in mm (ft)	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l (cu ft)	520 (18.4)
Largest luggage capacity - behind the 1st seat row in l (cu ft)	1490 (52.6)

\* Figures depend on the equipment selected.