

FIAT GRANDE PANDA		RED (ELECTRIC)	LA PRIMA (ELECTRIC)	POP (HYBRID)	ICON (HYBRID)	LA PRIMA (HYBRID)
DIMENSIONS	Length [mm]	3.999	3.999	3.999	3.999	3.999
	Height [mm]	1.570	1.573	1.586	1.586	1.585
	Height (w/ Antenna) [mm]	1.581 on antenna fixed base	1.615 on roof rails	antenna not present	1.598 on antenna fixed base	1.629 on roof rails
		(1.801 on antenna removable part)	(1.803 on antenna removable part)		(1.818 on antenna removable part)	(1.818 on antenna removable part)
	Width [mm]	1.763	1.763	1.763	1.763	1.763
	Width (w/ Mirrors) [mm]	2.017	2.017	2.017	2.017	2.017
	Wheelbase [mm]	2.540	2.540	2.540	2.540	2.540
	Wheelsize	TOD 632	TOD 638	TOD 652	TOD 652	TOD 658
	Front Overhang [mm]	788	788	788	788	788
	Rear Overhang [mm]	671	671	671	671	671
	Ground Clearance [mm, standard A]	137	137	137	137	137
	Boot volume [L]	361 l	361 l	412 l	412 l	412 l
		(350 liquid above carpet+11 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet+11bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)
	Boot volume w/ folded seats [L]	1.315 l	1.315 l	1.366 l	1.366 l	1.366 l
(1.304 liquid + 11 bricks below trunk carpet without tyre kit cargo box)		(1.304 liquid + 11 bricks below trunk carpet without tyre kit cargo box)	(1.304 liquid + 62 bricks below carpet without tyre kit cargo box)	(1.304 liquid + 62 bricks below carpet without tyre kit cargo box)	(1.304 liquid + 62 bricks below carpet without tyre kit cargo box)	
Tire Information	205/55R16	205/50R17	205/60R16	205/60R16	205/55R17	
Number of Seats	5	5	5	5	5	
BRAKES	Front	Disc	Disc	Disc	Disc	
	Rear	Disc	Disc	Disc	Disc	
	Front	Mac Pherson	Mac Pherson	Mac Pherson	Mac Pherson	
SUSPENSIONS	Rear	Twist Beam	Twist Beam	Twist Beam	Twist Beam	
	Power (torque max / Absorption)	75Nm (100A max)	75 Nm (100A max)	75Nm (100A max)	75Nm (100A max)	
STEERING	Ratio	51,5 mm/rev	51,5 mm/rev	51,5 mm/rev	51,5 mm/rev	
	Turn lock to lock (revs / deg)	3,1 / 1118	3,1 / 1118	3,1 / 1118	3,1 / 1118	
	Kerb to kerb turning cycle [m]	10,9	10,9	10,9	10,9	
WEIGHTS	Kerb Weight [kg]	1.532	1.554	1.315	1.327	
	Weight Standard A [kg]	1.457	1.479	1.240	1.272	
	Max Payload (including driver) [kg]	453	431	460	448	
	Battery [kg]	350	12	12	12	
	Towing [kg]	550	550	600	600	
	Max Power [kW]	83	83	74	74	
PERFORMANCES * provisional data under homologation	Max Power [CV]	113	113	100	100	
	Max Torque [Nm]	122	122	205	205	
	Traction	FWD	FWD	FWD	FWD	
	WLTP Consumption - Combined [kWh/100km]	16,8	16,8	-	-	
	WLTP Range - Combined [km]	320	320	-	-	
	CO2 Emissions - Combined [g/km]	-	-	116	115	
	Consumption - Combined [L/100 km]	-	-	5,4*	5,4*	
	Top Speed [km/h]	132	132	160*	160*	
	Acceleration 0-100 km/h [s]	11	11,5	10*	10*	
	Acceleration 0-50 km/h [s]	4,2	4,2	-	-	
	Technology	LFP	LFP	NMC	NMC	
BATTERY AND CHARGING	Total Voltage (Volts)	400V	400V	48V	48V	
	Battery Capacity [kWh]	44kWh	44kWh	0,876kWh	0,876kWh	
	Battery Capacity (Net) [kWh]	43,8	43,8	-	-	
	Charge Port	CCS Type2	CCS Type2	-	-	
	AC On-Board-Charger [kW]	7kW (11kW + NO spiral cable OPT)	7kW (11kW + NO spiral cable OPT)	-	-	
	DC Fast Charger [kW]	100kW	100kW	-	-	
	Charging Time [h:min] (AC 7kW - 20-80%)	04:20	04:20	-	-	
	Charging Time [h:min](AC 11kW - 20-80%)	02:50	02:50	-	-	
	Charging Time (DC 100kW - 20-80%)	00:27	00:27	-	-	
	Type	M2 EDM	M2 EDM	EB2LTEDH2 3 CYL TURBO	EB2LTEDH2 3 CYL TURBO	
ENGINE	Displacement [cm³]	-	-	1.2l	1.2l	
	Euro Emission Class	-	-	€6.4	€6.4	
	Gearbox	-	-	eDCT	eDCT	
	Fuel Tank [L]	-	-	44l	44l	